

"ASCENT" Series ILT-1X2

International Light Technologies has provided innovative design and engineering solutions for LED lighting applications for over 45 years. Let us provide you the quality, performance and cost effective LED solutions you require.

Applications:

- Channel Letters: face and halo.
- Internally Illuminated Sign Cabinets
- Architectural Lighting.
- Cove and Accent Lighting.

Features:


- 2 SMD LED's per module.
- 3 modules per ft, 10ft per strip to minimize cost.
- Low profile-under 1/4 inch.
- 3M VHB double faced tape.
- Mechanical fasteners for a secure installation included.
- Low power draw, able to power 180 white modules on a 12 volt 60 watt power supply.
- Conformal coated board under protective PVC housing to insure water-resistance.
- UL Listed in US and Canada.




Specifications:

PART #	Description	Operating Voltage	Current (mA)	Wattage	LED's / Module	Color	Peak Wavelength (nm)	Beam Angle	Module Dimensions (LxWxH)	Luminous Flux (lm/ft)	Qty 60 watt class 2 power supply
	See Ascent "Gen 2" For White										
ILT-1X2-R	Red SMD LED Module	12V	20	0.24	2	Red	623	140	1.38"x0.7"x0.19"	18	240 modules
ILT-1X2-A	Amber SMD LED Module	12V	20	0.24	2	Red	609	140	1.38"x0.7"x0.19"	9-Jun	240 modules
ILT-1X2-Y	Yellow SMD LED Module	12V	20	0.24	2	Yellow	590	140	1.38"x0.7"x0.19"	9	240 modules
ILT-1X2-G	Green SMD LED Module	12V	20	0.24	2	Green	520	140	1.38"x0.7"x0.19"	15	240 modules
ILT-1X2-B	Blue SMD LED Module	12V	20	0.24	2	Blue	465	140	1.38"x0.7"x0.19"	9	240 modules

Mechanicals:



Circuit Diagram:



For additional information call:
Joe Reis at **978-818-6180** ext 214

For a Quote and Population
layout send PDF. drawings to:
jreis@intl-lighttech.com

To order online go to: intl-lighttech.com.

10 Technology Drive Peabody, MA 01960
978-818-6180, fax 978-818-6181 www.intl-lighttech.com

